

8879-RF/CP Cable, Pipe, Line and Fault Locator

Rycom Instruments® makes utility locating as accurate as you need, as simple as you want.

- 2 passive frequencies of 50/60 Hz, and RF/CP allow locates of live utilities without the use of a transmitter
- 3 active frequencies of 815 Hz, 8 kHz, and 82 kHz allow accurate tracing in congested areas or the length of a single line
- Powerful 2.6 watt tracing signal is reliable for direct connection, transmitter and coupled induction
- Backlit digital display for low-light reading
- Triple antennae with push button depth and current measurement
- Optional rechargeable 12.6 volt sealed lead acid battery or 8 "D" cells
- Weather proof membrane buttons
- Made in the U.S.A.

The 8879-RF/CP cable, pipe, line and fault locator offers utility locators three active frequencies – 815 Hz, 8 kHz, and 82 kHz – ensuring adequate signal is applied to buried utilities in any environment. Multiple active frequencies allow the user to accurately locate with a minimum of "ghosting" to adjacent lines while maintaining the ability continue locating past faults and around conduit bends. Passive frequencies identify "live" and charged lines by their naturally occurring electromagnetic fields. The 8879-RF/CP offers two passive frequencies – 50/60 Hz and your choice of RF (radio frequency) or CP (cathodic protection) – allowing line locating without the use of a transmitter.

Updated transmitter functions include improved transmitter induction, dual-frequency coupled induction at 8 kHz and 82 kHz, and automatic impedance matching for direct connections. The 2.6 watt transmitter has the ability to simultaneously apply an 815 Hz and 82 kHz frequency to a utility. From one transmitter setting the user can locate the main line as well as other services by "lighting up" the entire site. This set-and-forget feature saves you time and money by reduc-

ing the need to repeatedly relocate the transmitter. All functions are accessed via weather-proof membrane buttons and both user input and transmitter status are verified with audible responses.

The ergonomically designed and balanced 8879 receiver provides instant push-button depth up to 15 feet and current measurement to help identify target utilities in crowded easements. Proximity cues to the tracing signal are given to the user through either peak or null tone modes while the backlit digital display provides both relative and actual signal strength.

The 8879-RF/CP can quickly and simply locate line when faults when used with the optional "A-frame" GRP (ground return probe). As the operator moves towards the fault the receiver will respond with rapidly peaking signal. When the "A-frame" is placed directly over the fault, the receiver will provide a null response.

Conduit pinches can be located using the optional Sondes. Operating on active frequencies of 815 Hz or 8 kHz, Rycom Instruments® Sondes are pushed into non-pressurized conduits and pipes until they reach the point of pinch or blockage. Traceable 20 feet in the air and 10 feet in cast iron, the 8879-RF/CP receiver will identify the precise location of the line blockage.

Rycom Instruments®, Inc. locators are designed and manufactured to make utility locating as accurate as you need and as simple as you want. For more information on the 8879-RF/CP, or any other Rycom Instruments® product, please call us toll free at 1-800-851-7347 or visit us online at www.rycominstruments.com.



Each 8879-RF/CP comes complete with a 2.6 watt transmitter, multi-function digital receiver, ground rod, red/black test leads, AC and DC battery charger, locating basics training video, manual and carrying cases.

RYCOM
instruments, inc.

www.rycominstruments.com
Accurate Utility Locating Made Simple

8879-RF/CP Specifications

Transmitter

Operating Frequencies: 82 kHz, 8 kHz, 815 Hz

Indicators: AC load assistance measurement, low battery indicator with modulated low battery warning

Load Matching: Automatic from 5 ohms to 2000 ohms

Output Power:

Frequency	Normal	High
815 Hz	0.6 W	2.6 W
8 kHz	0.6 W	2.6 W
82 kHz	0.2 W	1.0 W
Both (815 Hz + 82 kHz)	.12 W + .06 W	1.33 W + .67 W

Power Source: 12 V, 7 amp-hour maintenance free sealed lead acid battery with 120 V AC wall mount charger and DC truck charger or 8 "D" cell batteries

Battery Life: (dependant on load, frequency, power setting)
Rechargeable: continuous, 10-20 hours intermittent, 50-70 hours with 400 to 1200 rechargeable cycles
Disposable: continuous, 8-15 hours intermittent, 40-60 hours

Operating Temperature: -4° F to 133° F (-20° C to 55° C)

Size: 16" x 6.32" x 6" (41 cm x 16 cm x 15 cm)

Weight: Rechargeable: 11.5 lbs (5 kg)
Disposable: 8 lbs (3.6 kg)

Receiver

Operating Frequency: 82 kHz, 8 kHz, 815 Hz, 50/60 Hz, RF/CP

Antenna Mode: Peak, pin-point peak, and null

Display Indicators: Backlit LCD bar graph, low battery, signal strength, mode and function indicators

Audio Indication: Variable pitch response

Current Measurement: Display indicates relative current

Power Source: 6 "C" cell batteries

Battery Life: Continuous: 40 hours intermittent: 82 hours

Signal Strength: LCD bar graph, absolute signal strength readout 0-999

Gain Control: Manual up/down gain adjustment or automatic centering

Dynamic Range: 126 dB

Depth Measurement: Push-button readout to 15 feet or manual triangulation method

Operating Temperature: -4° F to +133° F (-20° C to +55° C)

Size: 30.3" x 9.4" (77 cm x 24 cm)

Weight: 3 lbs (1.3 kg)



WARRANTY: One-year warranty from date of delivery against defects in material and workmanship (EXCEPT BATTERIES) on all instruments. This warranty is void if, after having received the instrument in good condition, it is subjected to abuse, unauthorized alteration or casual repair. We will repair or replace products that prove to be defective during warranty period. NO OTHER WARRANTY IS EXPRESSED OR IMPLIED. THE WARRANTY DESCRIBED IN THIS PARAGRAPH SHALL BE IN LIEU OF ANY OTHER WARRANTY, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. WE ARE NOT LIABLE FOR CONSEQUENTIAL DAMAGES. **Terms:** Net 30 days, Missouri sales tax charged where applicable. **Shipping & Delivery:** All orders are FOB Raytown, MO. Specifications subject to change without prior notice.

RYCOM Instruments®, Inc. is a leading manufacturer and global supplier of cable, pipe and fault locating equipment. Established in 1946, RYCOM Instruments® Inc. maintains a state-of-the-art production facility and engineering department. Our guarantee is to deliver our customers a superior product and the locating equipment they need.

RYCOM Instruments®, Inc. locating devices are designed and manufactured to make utility locating as accurate as you need, and as simple as you want.



9351 East 59th Street • Raytown, MO 64133-3895, USA

800-851-7347 • 816-353-2100 • FAX 816-353-5050

E-mail: rycom@rycominstruments.com

www.rycominstruments.com

© 2006 Rycom Instruments®, Inc. All rights reserved.