



LXP-10B

Index: WMXXLXP10B

Light meters

Description

The new LXP digital light meter family allows for a very precise measurement of illuminance. Thanks to very high resolution (resolution 0.01 lx) allows for escape route emergency light measurement. All of three light meter have built-in memory for measurement result storing, and additional function making work much easier.

Specifications

The most important features:

- Measurement resolution 0.01 lx (0.001 fc).
- High accuracy and fast response.
- Data-hold function for holding measuring values.
- Automatic zeroing.
- No need for correction factors calculating for different light sources thanks to a very good fit spectral sensitivity guaranteeing the correct measurement of intensity of the illumination regardless of the nature of radiation.
- Peak-hold function for tracing the peak signal of light pulse with duration longer than 0.1 s and less than 1 s.
- Capable of selecting measuring mode in Lux or FC scale alternatively.
- Auto power off (5,10 or 15minutes) or disable AUTO power off.
- Maximum and minimum measurements.
- Relative reading.
- Easy to read large backlit display
- USB output connect with PC.
- Data transmission via radio connection using an optional adapter OR-1.
- Five measurement ranges.
- Built-in memory - 999, with can be checked in the meter or PC.
- 16000 values records data logger (traceable only in PC)

Illuminance measurement probe LP-10B:

Display Range [lx]	Resolution [lx]	Spectral uncertainty	Accuracy
0...39,99	0,01	f1 < 6%	±(5 % + 5 digits)
40,0...399,9	0,1		
400...3999	1		
4,00 k...39,99 k	0,01 k		
40,0 k...399,9 k	0,1 k		

Display Range [fc]	Resolution [fc]	Spectral uncertainty	Accuracy
0...3,999	0,001	f1 < 6%	±(5 % + 5 digits)
4,00...39,99	0,01		
40,0...399,9	0,1		
400...3999	1		
4 k...39,99 k	0,01 k		

- display result in lx or fc
- meter class B

Rated operational conditions:

- operating temperature: 0...50°C,

- operating humidity: 0% to 80% RH,
- storage temperature: -20...70°C,
- storage humidity: 0% to 70% RH.

Other technical data:

- display: 3¾ digit LCD with high speed 40 segment bargraph,
- over range indication: „OL” displayed,
- spectral response: CIE photopic (CIE human eye response curve),
- cosine response (f2'): ±3%,
- sampling rate: 1,3 times/sec,
- power supply: battery 9V or rechargeable battery 8,4 V,
- photo detector: one silicon photo diode and spectral response filter,
- memory: 999 results
- photo detector lead length: approx. 150cm,
- photo detector dimensions: 115 × 60 × 20mm,
- meter dimensions: 170 × 80 × 40mm,
- weight: 390g,
- data transmission: USB cable or wireless radio interface OR-1.