


Soldering Irons and Tips

Electronically Controlled Low Voltage Soldering Irons




| Order No. | Model | Description |
|---------------|---------|--|
| 005 33 135 99 | WSP 150 | Soldering set 150 W , 24 V The WSP 150 is specially developed for soldering tasks with extremely high heat requirements. The 150 W heater power combined with optimal heat transfer to the soldering tip gurantee high performance capability. |
| consists of: | | |
| 005 29 170 99 | WSP 150 | Soldering iron 150 W, 24 V with soldering tip LHT F |
| 005 15 027 99 | KH 27 | Safety rest |


Soldering Tips for WSP 150



| Order No. | Model | Description | Width A | Length B |
|---------------|-------|-------------|---------|----------|
| 005 44 455 99 | LHT C | Chisel | 3,2 mm | 1,2 mm |
| 005 44 452 99 | LHT D | Chisel | 4,7 mm | 1,8 mm |
| 005 44 451 99 | LHT E | Chisel | 6,7 mm | 1,8 mm |
| 005 44 450 99 | LHT F | Chisel | 9,3 mm | 1,8 mm |




| | | | | |
|---------------|--------|-------------|-------|------|
| 005 44 462 00 | LHT DX | Chisel bent | 5 mm | 2 mm |
| 005 44 461 00 | LHT EX | Chisel bent | 7 mm | 2 mm |
| 005 44 460 00 | LHT FX | Chisel bent | 10 mm | 2 mm |



| | | |
|---------------|-----------|---------------------------------------|
| 005 44 456 00 | LHT D 45° | Sloped 45° for solar panel production |
|---------------|-----------|---------------------------------------|



| | | |
|---------------|--|---|
| 005 44 454 00 | | LHT Screw in tip with outside thread M8 |
|---------------|--|---|



| | | |
|---------------|--|---|
| 005 44 453 99 | | LHT Measuring tip for thermo element \varnothing 0,5 mm |
|---------------|--|---|

| Order No./Model | Description |
|-----------------|---|
| 005 30 060 99 | Soldering iron 80 W, 24 V, for MT 1500 soldering station, w/o tip (spare part) |

